VERTICAL SLIDING WINDOWS (HERITAGE MK 2)

OPERATING INSTRUCTIONS

OPENING SASHES

To slide lower sash up:

Unlock Fitch Catch (located on top of lower sash) with key and then fully rotate lever to the right. Using the finger pulls, located on the bottom rail of lower sash, slide up to required position.

To slide upper sash down:

Firstly slide the lower sash up (as above). Using the D Handles, located outside on the bottom rail of upper sash, slide down to required position. You may now close bottom sash if required.

Please note:

If window is fitted with Limit Stops the sashes will only slide to a predetermined point. To allow the sash to fully open, the Limit Stops have to be unscrewed anti-clockwise using the key provided (Rola type) or pressed home and locked back by turning the key (Sharks Fin type).

CLEANING OUTSIDE OF WINDOW

Slide lower sash up by approximately 50mm (2 inches). Slide the 2 buttons which are located on the top of the lower sash towards each other, and gently pull top of sash into the room. Built in restrictors arms are fitted to allow the sash to rest in a position suitable for cleaning. Now slide the upper sash down by 50mm. Slide the 2 buttons which are located on the top of the upper sash towards each other and gently pull top of sash into the room. Built in restrictors arms are also fitted to the upper sash. The outside of the window can now be cleaned.

On a regular basis all PVCu surfaces should be washed down with warm soapy water. Abrasive cleaners should NOT be used as these will remove the natural skin of the PVCu and render it less resistant to the atmosphere. For stubborn stains, GENTLY use a good quality car polish. Similarly do not use abrasive materials on painted, anodized or lacquered components.

If windows have decorative Georgian bar, care should be taken whilst cleaning to prevent possible damage. All weathering gaskets and seals should be kept clean. If these become dislodged they can easily be pushed back into position, but if damaged they will have to be replaced to maintain product performance.

PRODUCT GUARANTEE

Only authorised personnel should carry out any remedial work or adjustment to any of the products installed. Please contact us for advice and assistance - especially if the item is covered by warranty.

For further assistance, call 01702 613733

11-14 Fletchers Square, Temple Farm Industrial Estate, Southend-on-Sea, Essex SS2 5RN

Telephone: 01702 613733 Fax: 01702 613367 **www.climatec-windows.co.uk**